

MASSIMO

400

Composition

100% PES

Weight

 $320 \text{ g/m}^2 + /- 5\%$

◆ Width

144 cm +/- 2 cm

Article

Furniture fabric



Care instructions











Product characteristics in accordance with the PN-EN 14465:2005+A1:2007

| Characteristics | Standard | Standard value | Category |
|--|---|----------------|----------|
| Seam slippage resistance | EN ISO 13936 -2 (mm) | ≤4 | A |
| Tear strength | EN ISO 13937 -3 (N) | ≥40 | A |
| Tensile strength | EN ISO 13934 -1 (N) | ≥400 | B |
| Abrasion resistance | EN ISO 12947 -2 (rubs) | ≥40 000 | A |
| Pilling resistance | EN ISO 12945 -2 (assessment after 5000 rubs) | ≥4 | B |
| Colour fastness to rubbing dry and wet | EN ISO 105-X12 | ≥4-5 | A |
| Cigarette test | PN-EN 1021-1 | | |

^{1.} Pilling is a natural process; it is not possible to eliminate it completely.

^{2.} For technological reasons fabric colour may differ from that in the catalogue.

^{3.} Dark and intensive fabric colours will migrate onto the light colours.

^{4.} The results of the Technical Specification are average results obtained during the tests.

^{5.} Exposure to UV rays may cause change of colours.